

CARATTERISTICHE
SPECIFICATION

Hand driven spur gear winches.

- Safe and robust hoisting winch, in compliance with EN 13157 and DIN 15020.
- Static safety factor 4.
- Adjustable crank, with ergonomic plastic grip.
- Load pressure brake with double ratchet system.
- Maintenance free bearing.
- Cable outlet to left, right and top side.
- As standard grey RAL 7035 painted or zinc-plated finish (TL 1000 and TL 1500 stainless steel).
- Operating temperature: -20°C / 40°C.

OPTION

- Atex certified
Ex II 3GD IIA T3 suitable for zone 2 and 22
- Two or more compartments (only TL 1000-1500).



Argani manuali con riduttore a ingranaggi.

- Costruzione robusta e sicura, in accordo a EN 13157 e DIN 15020.
- Coefficiente di sicurezza 4.
- Leva di comando regolabile, con impugnatura ergonomica in gomma.
- Freno a pressione di carico con doppio saltarello di sicurezza.
- Cuscinetti lubrificati a vita.
- Uscita fune verso sinistra, destra e verso l'alto.
- Disponibili di serie verniciati grigio RAL 7035 o zincati (TL 1000 e TL 1500 di acciaio inossidabile).
- Temperatura di lavoro: -20°C / 40°C.

SU RICHIESTA

- Versione Atex Ex II 3GD T3 per zona 2 e 22
- Due o più compartimenti fune (solo TL 1000- 1500).



TL 150



TL 300 - TL 600



TL 1000 GR - TL 1500 GR



TL 1000 SS
TL 1500 SS



Saltarello di sicurezza.
Ratchet system.



TL 1000 - TL 1500
Punti di fissaggio.
Lashing system.

